



Wholesale FC - SC Variable Fiber Optic Attenuator to Attenuate FTTH /CATV

Our Product Introduction

for more products please visit us on polyknitfabric.com

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: DYS/OEM
- Certification: RoHS, ce
- Model Number: FC
- Minimum Order Quantity: 10 pieces
- Price: \$1.00 - \$10.00/pieces
- Packaging Details: Plastic box + carton / customized
- Supply Ability: 20000 Piece/Pieces per Day



Product Specification

- Type: Fiber Optic Attenuator, Male To Female
- Use: FTTH
- Network: 4g, 3G
- Product Name: FC Variable Fiber Optic Attenuator
- Connector Gender: FC Male To Female
- Attenuation Level Range: 0~30dB
- Return Loss(dB): PC:≥50 UPC: ≥55 APC: ≥60
- Connector Type: LC SC FC ST
- Application: (Data Center)
- Material: Metal , Plastic
- Operating Wavelength: 1260nm~1620nm
- Operating Temperature: -40~80
- Port: Shenzhen Or HK



More Images



Product Description

Product Description

Wholesale FC Variable Fiber Optic Attenuator to Attenuate FTTH /CATV

Fiber optic attenuators are used in the fiber optic links to reduce the optical power at a certain level. Commonly used fiber optic attenuators are the female to male type, which is also called a plug fiber attenuator. They are with ceramic ferrules and there are various types to fit different kinds of fiber optic connectors. Fixed value fiber optic attenuators can reduce the optical light power at a fixed level. Variable fiber optic attenuators are with adjustable attenuation range. There are also attenuation fiber optic patch cables available, their function is same as attenuators and are used inline.

Our Product Introduction



for more products please visit us on polyknitfabric.com



Product type	Coupler Attenuator Male to Female
Operation wavelength	SM: 1200 to 1600nm or 1310/1550nm MM: 850nm, 1300nm
Return Loss	≥ 50 db (PC) ≥ 55 db (UPC) ≥ 65 db (APC)
Attenuation Accuracy	± 0.5 db for 1 to 5db attenuation $\pm 10\%$ for 6 to 30db attenuation
Polarization Dependent loss	≤ 0.2 db
Mechanical endurance	>1000
Maximum optical Input power	200MW
Operating Temp Range	-40 to + 80degree



Fixed Fiber Optic Attenuator



Variable Fiber Optic Attenuator





Main Products



Fiber Optic Cable



Patch Cord & Pigtail



MPO/MTP



FTTX Cable Assembly



Fiber Optic Adapter



(FTTH) Terminal Box



(FTTH) PLC Splitter



(FTTH) Fast Connector

Our Company

DYS CERTIFICATE

1 One-stop Solution Service

2 Products made by DYS own factory with competitive price, good quality and fast delivery time

Reliability Testing Laboratory

- Manual Image Measuring Machine
- Automatic Insertion Force Testing Machine
- Tensile Testing Machine
- High Low Temperature Circulating Machine
- IP68 Pressure Water Immersion Testing Machine
- Fiber Bending and Torsion Testing Machine
- Salt Spray Testing Machine
- Collision Testing Machine
- Three Directions Vibration Test Machine



PACKING & DELIVERY



FAQ

1. Do you provide OEM ODM service?
Yes, we can print your logo or label on the products or on the box.
2. How can you guarantee the quality?
Build on our perfect quality management system, all of our products were 100% tested before the shipment.
3. What is your delivery time?
Generally, sample: 3-5 working days; formal order: 7-10 working days.
4. What's the method of shipment?
We accept all shipment, such as Delivery, ocean transport, land transport, airport transport.
5. What's the Payment?
We accept all payments, such as LC, TT, DP, DA, Paypal, Western Union, Money Gram.

[Product inquiry](#)

Send us inquiry, you will get full catalog.





Beijing Silk Road Enterprise Management Services Co., Ltd



13299345678



13299345678@163.com



polyknitfabric.com

19 Xinjian Gongmen Road, Haidian District, Beijing, China