
## Optical FC SC ST LC Bare Fiber Adapter for bare fiber OTDR testing



Basic Information		
<ul> <li>Place of Origin:</li> </ul>	Guangdong, China	
<ul> <li>Brand Name:</li> </ul>	DYS/OEM	
<ul> <li>Certification:</li> </ul>	RoHS, ce	
Model Number:	LC Bare Fiber Adapter	
Minimum Order Quantity:	100 pieces	
Price:	\$3.00 - \$8.00/pieces	
<ul> <li>Packaging Details:</li> </ul>	Plastic box or according to custom	



request 20000 Piece/Pieces per Day • Supply Ability:



for more products please visit us on polyknitfabric.com

### **Product Specification**

• Type:	Fiber Adapter & Connectors
• Use:	FTTH
<ul> <li>Warranty Time:</li> </ul>	5
<ul> <li>Network:</li> </ul>	4g, 3G
Product Name:	LC/UPC Fiber Optic Adapter Square Type Bare Fiber Adapter
<ul> <li>Adapter Type:</li> </ul>	LC,FC,ST, SC
Quality:	High Quality Optical Adapter
Sleeve:	Zirconia
Color:	Green And Blue
Return Loss:	≥45dB(PC), ≥50dB(UPC), ≥65dB(APC)
<ul> <li>Insertion Loss (Typical):</li> </ul>	≤0.2dB

- >1000 Times • Durability:
- Application:
- Storage Temperature: -45~85°C



### More Images



Fiber Optic Testing, Fiber Optic Cable Repair

### **Product Description**

### **Product Description**

### Optical FC SC ST LC Bare Fiber Adapter for bare fiber OTDR testing

Bare fiber adapter i a very efficient media to connect bare fiber to fiber optic devidce, it usually used in installation to test links. One side of the bare fiber adapter is the bare fiber, the other side is the fiber optic connector to plug into equipment. FC,ST,SC,LC bare fiber adapter available.

# **Our Product Introduction**

for more products please visit us on polyknitfabric.com



- FEATURES

- 1. Insertion Loss Typical: ≤0.2dB;

   2. Return Loss: ≥50dB;

   3. Exchangeability: ≤0.2dB;

   4. Repeatability: ≤0.2dB;

   5. Durability: >1000 times;

   6. Operating Temperature: -40~+80C

   7. Storage Temperature: -45~85C







Hybrid Adapter

SC Adapter Parameter Unit Insertion Loss Typical dB ≤0.2 Return Loss dB ≥0.5 Exchangeability dB ≤0.2 Repeatability dB ≤0.2 Time Durability 1000 s Operating Temperature °C -40~80 Storage Temperature °C -45~85

LC Adapter Bare fiber adapter



# OUR EXHIBITIONS



13299345678
 13299345678@163.com
 polyknitfabric.com
 19 Xinjian Gongmen Road, Haidian District, Beijing, China